

PRODUCT DATA SHEET iW4R





iW4R

PRODUCT DESCRIPTION

Nothing is faster than light. And no lamp is ready for use faster than the iW4R - the rechargeable pocket work light! Hardly larger than a pen, it illuminates every step at work with just the right light. Built-in magnets mean the flexible bracket can be attached in different ways to direct the light at the right angle. With the battery indicator you will always know much longer the iW4R will last - but with up to four hours of power you won't be left in the dark anytime soon.

- Compact pocket size (20 x 156)
- Two light sources, spotlight with reflector lens and floodlight with two light functions
- Battery indicator
- Built-in magnet to easily attach to metal surfaces (e.g. steel beams or motors)
- Tilt mechanism for flexible orientation for optimal illumination of the workspace

| | 7 |) |
|---------|----|------------------|
| Y WA | EA | R NTY⁴ |

| TECHNICAL DATA | |
|------------------------------|----------------|
| Width [mm] | 27 |
| Depth [mm] | 20 |
| Height [mm] | 157 |
| Weight incl. batteries [g] | 72 |
| Weight without batteries [g] | 59 |
| Focus function | No |
| Primary material | Other plastics |
| Cartridge | No |

| POWER SUPPLY | |
|--|--|
| Power source type | Rechargeable battery |
| Battery quantity | 1 |
| Battery type | Li-ion |
| Battery replaceable | No |
| Total battery voltage [V] | 3.7 |
| Total battery capacity [mAh] | 750 |
| Total battery energy ² [Wh] | 2.8 |
| Rechargeable | Yes |
| Charging time ⁵ [min] | 150 |
| Charging technology | Internal |
| Energy status indicator | Battery Indicator, Charge Indicator |

FURTHER SPECIFICATIONS

| IP class | IP54 |
|--------------------------------|------------|
| Drop test (drop height) [m] | 1 |
| Working temperature range [°C] | -10 to +40 |

LIGHT FUNCTIONS

Low Power, Power

| LIGHT SOURCE | Flood | Spot |
|-----------------------------|--------------|--------------|
| Amount LEDs | 1 | 1 |
| LED type | 8W COB LED | Power LED |
| Color | White | White |
| Color temperature [K] | 5400 to 6600 | 5400 to 6600 |
| Color rendering index (CRI) | 80 | 70 |

| LIGHT VALUES - Flood | | | | |
|--------------------------------|-------|-------|---------------------|--|
| | Boost | Power | Mid Power Low Power | |
| Light output ¹ [lm] | | 150 | 75 | |
| Run time ¹ [h] | | 2 | 4 | |

| LIGHT VALUES | - Spot | | | |
|--------------------------------|--------|-------|-----------|-----------|
| | Boost | Power | Mid Power | Low Power |
| Light output ¹ [lm] | | 75 | | |
| Run time ¹ [h] | | 2 | | |

SWITCH

Switch





iW4R

PACKAGING AND LOGISTICS



PACKAGING INFORMATION

| Type of packaging | Box |
|-----------------------|-------------|
| Scope of delivery | USB cable |
| Item No. | 502003 |
| Customs tariff number | 85131000000 |
| Color | black |
| MSRP price (€) | 44.90 |

| SINGLE PACKAGE | |
|---------------------------|----------------|
| Dimensions W x H x D [cm] | 5 x 16.6 x 3.2 |
| Gross weight [g] | 135.2 |
| GTIN-13 | 4058205016261 |

INNER CARTON

| 20.5 x 5.4 x 17.5 |
|-------------------|
| 882 |
| 4058205016278 |
| |

6

| EXPORT CARTON | |
|---------------------------|------------------|
| Unit | 60 |
| Dimensions W x D x H [cm] | 38.5 x 30.5 x 25 |
| Gross weight [kg] | 9.40 |
| GTIN-13 | 4058205016285 |
| | |





ACCESORIES

| PRODUCT CATEGORY | ITEM NUMBER | PRODUCT NAME | MSRP |
|------------------|-------------|------------------|---------|
| Charger / Cable | 0380 | USB Car Charger | 9.90€ |
| Charger / Cable | 502271 | USB Adapter 2.4A | 14.90 € |



iW4R

PRODUCT SERIES

The Ledlenser i-Series Work lights & spotlights

Powerful performance! Ready whenever you need to illuminate the darkness of your workshop or construction site: the Ledlenser i-Series work lights & spotlights - durable multi-purpose lights for true professionals! Whether you use a single spotlight or floodlight with wide coverage, with these professional lights you always have the right type of light at your fingertips. Compact, powerful and rechargeable - each model impresses during everyday use.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode". 2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the product series "Solidline", Ledlenser K1 and Ledlenser K2. The warranty does not apply to Defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Ledlenser GmbH & Co. KG, Kronenstr. 5 - 7, 42699 Solingen, Germany. More information: ledlenser.com/warranty

5) Charging time varies by hardware used.

